

PRODUCT SUMMARY

The FoxFury D3060 is a small format utility light with forward-focused lighting, right angle flood lighting, and strobe light. It can mount to drones or straps and rotate 360° for omni-directional light. The D3060 is waterproof and rechargeable.

D3060 FEATURES

- Two lights in one
- 30° front light, 60° dorsal light
- 360° swivel light
- 5700K white balanced LEDs
- Rechargeable LiPo battery recharges in 1.5 hours
- Waterproof and impact resistant
- Mounts with 3M Dual Lock Reclosable Fastener or customer-supplied strap
- Strobe mode meets FAA and global regulations for UAV night flight and anti-collision lighting
- Operating temperature range: -4°F (-20°C) to 300°F (149°C)

P/N 700-310-TC



MATERIALS

- Polycarbonate body with silicone switch
- Nylon rear and Base/MOLLE mount

WHAT'S INCLUDED

- Base/MOLLE Mount
- 3M Dual Lock Fastener, 1" (set of 2)
- USB-C Cable

WARRANTY

- One year
- 300 recharge cycles

DIMENSIONS

- 1.3 x 2.3 x 0.9 in (33 x 58 x 23 mm)
- 1.3 oz (37 g)

BATTERY

- Rechargeable LiPo battery system
- 3.7V, 560 mAh
- Lasts 1.5 - 3 hours
- Recharges in 1.5 hours

CERTIFICATIONS

- IPX6
- CE-EMC
- Meets NFPA 1971-8.6 (2013) requirements

LIGHT	MODE	LUMENS	BATTERY LIFE
FRONT LIGHT ONLY	HIGH	200	1.5 hours
	LOW	60	2.5 hours
	STROBE	200	2 hours
DORSAL LIGHT ONLY	HIGH	160	1.7 hours
	LOW	50	3 hours
	STROBE	160	2 hours
BOTH FRONT AND DORSAL LIGHTS	HIGH	N/A*	N/A*
	LOW	60 FRONT / 50 DORSAL	2 hours
	STROBE	200 FRONT / 160 DORSAL	1.5 hours

*Thermal protection circuit will automatically reduce the Dorsal Light to low mode when the Front Light is on high mode. The battery life for this setup is 1 hour.

D3060 IR FEATURES

- Two lights in one
- 30° front light, 60° dorsal light
- 360° swivel light
- Infrared Light, 400 mW
- Rechargeable LiPo battery recharges in 1.5 hours
- Waterproof and impact resistant
- Mounts with 3M Dual Lock Reclosable Fastener or customer-supplied strap
- Operating temperature range: -4°F (-20°C) to 300°F (149°C)

P/N 700-319



MATERIALS

- Polycarbonate body with silicone switch
- Nylon rear and Base/MOLLE mount

DIMENSIONS

- 1.3 x 2.3 x 0.9 in (33 x 58 x 23 mm)
- 1.3 oz (37 g)

BATTERY

- Rechargeable LiPo battery system
- 3.7V, 560 mAh
- Lasts 1.5 - 2.5 hours
- Recharges in 1.5 hours

WHAT'S INCLUDED

- Base/MOLLE Mount
- 3M Dual Lock Fastener, 1' (set of 2)
- USB-C Cable
- D Series Mount Set (P/N 700-319 IR only)

WARRANTY

- One year
- 300 recharge cycles

CERTIFICATIONS

- IPX6
- CE-EMC
- Meets NFPA 1971-8.6 (2013) requirements

LIGHT	MODE	mW	BATTERY LIFE
FRONT LIGHT OR DORSAL LIGHT ONLY	HIGH	400	1.5 hours
	LOW	150	2.5 hours
	STROBE	400	2 hours
BOTH FRONT AND DORSAL LIGHTS	HIGH	N/A*	N/A*
	LOW	150	2 hours
	STROBE	400 FRONT / 150 DORSAL	1.5 hours

P/N 700-310-TC



P/N 700-319

